

TP6/V/1-EC

CUTTING BENDING
MACHINE FOR AXIAL
COMPONENTS VERTICAL
MOUNTING



81.0L01 STANDARD



The TP6/V/1-EC machine is designed for cutting and bending taped axial components for vertical mounting. It operates components with lead diameters from 0,5 to 0,8mm (.019 to .031"). The bending pitch is determined by the bending cam supplied and it can be changed by replacing this cam with one having different thickness.


TP6/V/1-EC machine is only supplied manual version and for taped components.

WARNING: FOR PITCH 2,54 MM MINIMUM LENGTH BETWEEN BODY AND TAPE SHALL BE: LENGTH OF THE BODY PLUS 12 MM. THE LENGTH OF THE LEAD FOR THE LARGER PITCHES SHALL BE INCREASED BY RELATION

PRODUCTION:
TAPED: 50.000


TP6/V/1-EC STANDARD VERSIONS

81.OL01- PITCH 2,54 MM




| | MM | | IN | |
|----------|----------|-----|--------|------|
| A | min | max | min | max |
| A | 2 | 6 | .078 | .236 |
| L | | 15 | | .590 |
| F | 3 | 8 | .118 | .314 |
| D | 0,5 | 3 | .019 | .118 |
| d | 0,5 | 0,8 | .019 | .031 |
| P | 2,54 fix | | .1 fix | |

81.OL03- PITCH 3,8 MM




| | MM | | IN | |
|----------|---------|-----|---------|------|
| A | min | max | min | max |
| A | 2,5 | 6 | .098 | .236 |
| L | | 15 | | .590 |
| F | 3 | 8 | .118 | .314 |
| D | 0,5 | 5 | .019 | .196 |
| d | 0,5 | 0,8 | .019 | .031 |
| P | 3,8 fix | | .15 fix | |

81.OL04 - PITCH 5,08 MM



| | MM | | IN | |
|----------|----------|-----|--------|------|
| A | min | max | min | max |
| A | 3 | 7 | .118 | .275 |
| L | | 15 | | .590 |
| F | 3 | 8 | .118 | .314 |
| D | 0,5 | 8 | .019 | .314 |
| d | 0,5 | 0,8 | .019 | .031 |
| P | 5,08 fix | | .2 fix | |

81.OL05 - PITCH 7,62 MM



| | MM | | IN | |
|----------|----------|-----|--------|------|
| A | min | max | min | max |
| A | 4 | 7 | .157 | .275 |
| L | | 15 | | .590 |
| F | 3 | 8 | .118 | .314 |
| D | 0,5 | 10 | .019 | .393 |
| d | 0,5 | 0,8 | .019 | .031 |
| P | 7,62 fix | | .3 fix | |